



Mapecure SP

Film-forming curing compound in water emulsion for concrete

WHERE TO USE

To protect fresh concrete from rapid water evaporation caused by wind or sunlight and to reduce surface cracking.

Some application examples

Mapecure SP is especially recommended for protecting concrete structures such as:

- Industrial floors;
- Exterior paving (roads, parking lots);
- Airport runways;
- Renders;
- Dam faces;
- Bridges;
- Canals;
- Reservoirs.

TECHNICAL CHARACTERISTICS

Mapecure SP is a white water emulsion of special resins which forms an efficient curing film on concrete.

Mapecure SP provides reliable protection against rapid evaporation of water in concrete, whether exposed to direct sunlight or under severe rapid drying conditions caused by wind, low humidity, or high ambient or concrete temperatures.

Mapecure SP offers the following advantages:

- Less surface dusting;

- Less plastic shrinkage cracking;
- Elimination of traditional protection methods, such as spraying water, wet burlap sacks, wet sand;
- Fast and easy application;
- Lower labour costs and more efficient job-site management.

DIRECTION FOR USE

Mapecure SP should be applied to the surface of the concrete after bleeding water, if any, has disappeared. For industrial paving, **Mapecure SP** must be applied after the concrete has started to set.

For concrete formwork **Mapecure SP** must be applied immediately after stripping.

Preparing the product

Carefully stir **Mapecure SP** before applying.

Do not dilute **Mapecure SP**.

Applying the product

Apply **Mapecure SP** in one spray coat with low pressure sprayer, or roller, in a thin and even layer.

Cleaning

Spray tools must be cleaned with water before **Mapecure SP** dries.



TECHNICAL DATA (Typical Values)

Product as it is:	Ready-to-use
Consistency:	Runny fluid
Colour:	White
Density at +20 °C (kg/l):	1.00 ± 0.02
pH:	6.5 - 7.5
Specific action:	Concrete surface protection against rapid water evaporation
Brookfield viscosity at +23 °C:	< 0.05 mPa.s (shaft 1 – 20 rpm)
Application temperature:	+5 °C - +35 °C
Storage:	12 months in original sealed packaging
Hazard classification according to EC 88/379:	None.
Customs class:	2712 20 00

COVERAGE

70 – 100 g/m².

PACKAGING

25 kg drums

STORAGE

Store in closed containers; protect from frost and exposure to direct sunlight at temperatures between +5 °C - +35 °C.

FOR PROFESSIONALS.

N.B.

Although the technical details and recommendations contained in this product report correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical applications: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in every case, the user alone is fully responsible for any consequences deriving from the use of the product.



MAPEI GROUP CERTIFIED MANAGEMENT SYSTEMS (Quality, Environment and Safety)

MAPEI S.p.A. - ITALY				MAPEI FAR EAST Pte Ltd MAPEI MALAYSIA SON BHD		MAPEI s.r.o. - CZECH REP.
MAPEI FRANCE	MAPEI INC - CANADA	RESCON MAPEI AS - NORWAY		MAPEI KH. - HUNGARY	MAPEI ARGENTINA S.A.	MAPEI SUISSE SA

www.mapei.com